

TSK廠內 DESINA線材

更新日期:2011/04/11

品名	規格	AWG	mm ²	外徑	色
TSS-001-DN	UL 20276 7/0.18TA x 10P	26	0.178	10.0	紫色
TSS-002-DN	UL 20276 7/0.18TA x 50C	26	0.178	11.6	紫色
TSS-003-DN	UL 20276 40/0.08AC x 3P + 20/0.18TA x 1P	---		8.7	綠色
TSS-004-DN	UL 20276 7/0.18TA x 40C	26	0.178	10.4	紫色
TSS-004A-DN	UL 20276 7/0.18TA x 10C	26	0.178	6.7	紫色
TSS-008-DN	UL 20276 7/0.18TA x 20C	26	0.178	7.5	灰色
TSS-022-DN	VS-SB 870/0.18AC x 1C	---	22	11.7	橘色
TSS-023-DN	UL 20276 40/0.08AC x 7P	26	0.2	8.7	紫色
TSS-023B-DN	VV-SB 40/0.08AC x 10P	26	0.2	10.3	紫色
TSS-042-DN	UL 2464 12/0.18TA x 2P	23	0.3	7.8	紫色
TSS-085-DN	UL 2464 21/0.18TA x 8C	20	0.5	7.9	灰色
TSS-096-DN	UL 2464 21/0.18TA x 2C	20	0.5	5.6	黃色
TSS-140-DN	VS-SB 259/0.26AC x 1C	6	14	9.6	橘色
TSS-256-DN	UL 20276 17/0.16AC x 4C	22	0.3	5.1	黃色
TSS-276-DN	UL 2464 100/0.08AC x 10C	22	0.5	11.4	灰色
TSS-285-DN	UL 2586 700/0.08AC x 4C	12	3.5	13.8	橘色
TSS-287-DN	VS-SB 1600/0.08AC x 4C	9	8	18.6	橘色
TSS-369-DN	UL 20276 40/0.08AC x 3P + 100/0.08AC x 6C	---		9.0	綠色
TSS-380S-DN	VS-SB 703/0.26AC x 1C	---	38	14.1	橘色
TSS-407-DN	UL 20276 7/0.18TA x 25C	26	0.178	8.8	紫色
TSS-409-DN	UL 20276 60/0.08AC x 5P	23	0.3	8.2	綠色
TSS-409A-DN	UL 20276 60/0.08AC x 5P	23	0.3	8.2	紫色
TSS-411-DN	UL 2501 161/0.26AC x 4C	8	8	21.6	橘色
TSS-411A-DN	VS-SB 154/0.26AC x 1C	9	8	8.0	橘色
TSS-422-DN	UL 20276 40/0.08AC x 4P + 100/0.08AC x 1P	---		8.0	綠色
TSS-426-DN	UL 20276 40/0.08AC x 1P + 60/0.08AC x 5C	---		7.0	綠色
TSS-426A-DN	UL 20276 40/0.08AC x 2P + 20/0.18TA x 1P	---		8.1	紫色
TSS-426B-DN	UL 20276 40/0.08AC x 2P + 20/0.18TA x 1P	---		8.1	黃色
TSS-432-DN	UL 20276 100/0.08AC x 5P	22	0.5	9.4	綠色
TSS-435-DN	UL 2464 30/0.08AC x 4P	26	0.15	6.5	紫色
TSS-482-DN	UL 2464 60/0.08AC x 7P	24	0.3	8.8	灰色
TSS-484-DN	UL 20276 100/0.08AC x 2P + 40/0.08AC x 2P	---		8.3	綠色
TSS-516-DN	UL 2464 26/0.26TA x 2C	16	1.35	6.8	灰色
TSS-516A-DN	UL 2464 26/0.26TA x 2C	16	1.35	7.5	灰色
TSS-516-4A	UL 2517 266/0.08AC x 4C	16	1.3	6.4	橘色
TSS-518-DN	UL 2464 34/0.18TA x 2C	18	0.85	6.1	灰色
TSS-518A-DN	UL 2464 34/0.18TA x 2C	18	0.85	6.3	橘色
TSS-518C-DN	UL 2464 34/0.18TA x 2P	18	0.85	9.7	紫色
TSS-520-DN	UL 2464 21/0.18TA x 4C	20	0.5	6.8	灰色
TSS-520A-DN	UL 2464 21/0.18TA x 3C	20	0.5	6.4	黃色
TSS-520B-DN	UL 2464 21/0.18TA x 3C	20	0.5	6.1	橘色
TSS-520C-DN	UL 2464 21/0.18TA x 2C	20	0.5	6.1	綠色
TSS-520D-DN	UL 2464 21/0.18TA x 2C	20	0.5	5.7	紫色

TSK廠內 DESINA線材

更新日期:2011/04/11

品名	規格	AWG	mm ²	外徑	色
TSS-610-DN	UL 2586 105/0.26AC x 4C	10	5.5	14.4	橘
TSS-612-DN	UL 2586 66/0.26AC x 4C	12	3.5	13.1	橘
TSS-614-DN	UL 2586 50/0.25AC x 4C	14	2.5	12.3	橘
TSS-614-4	UL 2501 420/0.08AC x 4C	14	2.1	13.0	橘
TSS-616-DN	UL 2586 26/0.26TA x 4C	16	1.35	10.4	橘
TSS-616A-DN	VUR-SB 60/0.18AC x 4C	16	1.5	10.7	橘
TSS-704-DN	UL 20276 21/0.18TA x 2C+ 17/0.16TA x 6C	---		9.0	黃
TSS-866-DN	VS-SB 196/0.16AC x 4C + 40/0.18AC x 2C	---		13.9	橘
TSS-866-6C	XEUR-1BSP-SB 196/0.16TAx4C + 40/0.18TAx2C	---		15.1	橘
TSS-866A-DN	UL 2586 60/0.18AC x 4C	16	1.5	10.6	橘
TSS-866B-DN	VUR-1ABP-SB 60/0.18AC x 4C + 40/0.18AC x 2C	---		14.1	橘
TSS-866C-DN	XEUR-SB 196/0.16TA x 4C	12	4	14.0	橘
TSS-866D-DN	VS-1ABP-SB 500/0.08AC x 4C + 150/0.08AC x 2C	---		13.4	橘
TSS-867-DN	UL 20276 7/0.16TAx3P + 7/0.16TAx4C + 7/0.2TAx4C + 20/0.18TAx2C	---		10.7	綠
TSS-867B-DN	XEUR-3SSP-SB 7/0.16TAx(3P+4C) 21/0.18TAx2C	+	---	10.1	綠
TSS-867C-DN	XEUR-3SSP-SB 7/0.16TA x 3P + 40/0.18TA x 2P	---		10.6	綠
NP-586	UL 2501 34/0.18TA x 4C (UL+cUL)	18	0.85	9.7	橘
NP-587	UL 2464 17/0.16TA x 18C (UL+cUL)	22	0.5	10.7	灰
NP-588	UL 20276 12/0.18TA x 40C (UL+cUL)	23	0.3	11.0	灰
NP-589	UL 2464 60/0.08AC x 6P (UL+cUL)	23	0.3	8.8	綠
NP-594	UL 2464 17/0.16TA x 25C (UL+cUL)	22	0.5	9.7	黃